



GenoLabTEK



SMART-200

AUTO CHEMISTRY ANALYZER

- Constant 200 test/ hour with double reagent
- 80 reagent positions
- Automatic liquid level sensing, anti-collision protection.
- Integrated full closed optical system, multi wavelength simultaneous detection.
- New amorphous optical plastics reaction cups, perfect transmittance.
- Maintenance free semiconductor solid state refrigeration
- Friendly surface and easy to operation
- 4-stage, 2 times automatic washing system, Alkaline cleaning solution



GenoLabTEK

TECHNICAL SPECIFICATIONS

General information

Machine type	Random access, open reagent & locked reagent (optional)
Test speed	Constant 200 tests/hour (Mono reagent or double reagent)
Test principle	Colorimetric method, turbidimetry
Test method	1 point end, 2 point end, Fixed-Time, Kinetics
Calibration type	Linear & nonlinear

Sample unit

Sample tray	40 sample positions
Sample tube	Micro cup & test tube & blood collection tube can be used. (Ø 12 -13)mm * (25-100)mm
Sample volume	2-30µL, step by 0.1µL
Sample probe	Liquid surface detection, timely tracking for liquid volume.Collision avoidance
Sample barcode	Sample barcode reader (optional)

Reagent unit

Reagent tray	80 reagent positions (40 for R1 & 40 for R2), Non-stop cooling system with peltier pad inside, 24 hours 2°C-14°C, open system, could accept any reagent.
Reagent volume	20-300µl, step by 1µl
Reagent needle	Liquid surface detection, timely tracking for liquid volume. Collision avoidance.
Reagent barcode	Regent barcode reader (optional)

Reaction unit

Reaction tray	44 reaction cuvettes, new amorphous optical plastics reaction cups, perfect transmittance.
Reaction volume	150µl-330µl
Reaction time	10 minutes
Temperature	Peltier pad incubation system, reaction temperature (37°C ± 0.1 °C)

Mixing system

Mixer	paddle-type mixing, effective reducing of carry-over
--------------	--

Optical system

Light source	Halogen lamp
Wavelength	340nm; 405nm; 450nm; 505nm; 546nm; 578nm; 630nm; 700nm(4 more options)
Absorbance range	0-4.0 Abs
Resolution	0.0001 Abs

Operating system

Operation system	Windows XP, Windows 7, Windows 8, Windows 10
Data processing	Automatic calibration, test combination, effective time management of reagents, serum index, whole process detection, linear expansion of enzyme, blank deduction,dirty cuvette memory , cross infection prevention, patient information memory and association input, automatic report audit, data fuzzy query, report statistics and printing, reference range grading, alarm information classification, user operation privilege classification management.
Report printing interface	6 formats optional, support custom pattern TCP/IP network interface

Working conditions

Power supply	AC 110/220V ± 10%, 50/60 Hz, 650W
Water consumption	12L/hour(maximum)
Dimension	910mm * 650mm * 1120mm(L *W*H)
Weight	127.5kg